DOE / SNL Scaled Wind Farm Technology (SWiFT) Facility at TTU


Dr. Jonathan R. White

World-Class Wind Testing Facilities
Wind Energy Technology Department
Sandia National Laboratories
(505) 284-5400
jonwhit@sandia.gov






SANDIA NATIONA'



Outline


- ■DOE/SNL Objectives of Scaled WInd Farm Technology Facility
- SWIFT Overview
- Collaborative Partnerships
- Progress Updates






DOE/SNL Objectives of Scaled Wind Farm Technology Facility





Exceptional service in the national interest







DOE/SNL Objectives

Study of turbine to turbine interaction

- Tip vortices, wake growth, wake mixing, meandering wakes
- Inflow turbulence, low-level jets, advanced features


Advanced wind turbine rotor development

- Passive load control: bend-twist coupling, sweep-twist coupling, passive camber control, flat-back airfoils
- Active load control: smart rotor, nonlinear wind turbine control, smart turbine design
- Advanced sensing technologies: operational monitoring, structural health monitoring, prognostics

Aerodynamics, aero-elasticity, and aero-acoustics testbed

 Inboard aerodynamics, 3D blade flow, NUMAD / BPE design tool advancement, near-blade acoustic generation, acoustic propagation, acoustic beam-forming








Site Plan











Turbine Site Plan















Wind Resource Assessment




8 m/s at 77 m (7.5 m/s at 50 m)

Class 5 Wind Site!



South 180.5° Average




Proposed Test Turbine



Site Production

- •92 kW Average

- •7 m/s hub-ht. average
- •41% Capacity Factor



Modified Vestas V-27

- 300 kW (0 55 rpm)
- 13 m (43 ft) Blade Length
- Pitch Control in Region 3
- 30 m (98 ft) Tower Height
- •Reynolds Number ~2 × 10⁶
- Highly reliable




What is Research-Scale?

Research-Scale









Megawatt-Scale



- A cost-efficient size for which research can be directly scaled to larger, more costly and time-consuming sizes.
- Requirements:
 - Operation at Reynolds Number (scaling parameter) between 10⁶ and 10⁷
 - Tip speeds approaching 80 m/s for acoustics and large rotor projects
 - Variable-speed variable-pitch operation
 - Minimal cost and time associated with research operations
 - Highly reliable turbine
- Minimal restrictions on publication and intellectual property




Aerodynamic Scaling





Cost Efficiency





Crane Cost Comparison

Research Scale (225 kW)



<u>Costs</u> \$5,000 v. \$250,000

Scheduling

Days
Ahead


V. Ahead


Testing Risk
Low v. High

Megawatt Scale









Research-Scale

Examples of Success




"Light detection and ranging measurements of wake dynamic Part I & II" 2011






LIDAR Scanning of 95 kW Turbine Wake






Decomposition of Wake Deficit





CX / TX / BSDS Blade Family Study



Fabrication and Testing at the 115 kW Scale





Result: 24% reduction in damage
equivalent load and initiated industrial
use of carbon, flatback airfoils and twistbend coupling.
Sandia National Laboratories





SWIFT Partnerships












































DOE/SNL/TTU Partnership

- Wind Science and Engineering Research Center (WISE) has a 40 year history in wind-related research and development
- Unique Capabilities and Facilities






TEXAS TECH



Variable-Speed Upgrade

Fixed Speed







DOE/SNL
Variable
Speed
(Open-source)

Variable


Up to

55 RPM

(28 % increase)



Re-purposed Assembly Building







Site Construction










SWiFT










Anemometer Tower










Control Building











Refurbished Assembly Building



Experimental rotor preparation

Machine Shop





